



## PRODUCT DATA SHEET

# ANDEROL PQAA GREASE #2

## Food Grade Grease NLGI-2



### ADVANTAGES/BENEFITS

- Lubrication of friction bearings even at high temperatures and water exposure
- General-purpose food grade grease
- Lubrication of machinery in food and beverage industry
- Grease lubricated points in can seaming and bottling
- Excellent wear protection
- Prevents Rusting
- Good mechanical stability

### APPROVAL

**ANDEROL®** Food Grade lubricants are approved, recommended and field tested by many OEM's in the food processing, bottling, canning, meat processing, and pharmaceutical industries.

**ANDEROL®** Food Grade Lubricants are registered by NSF International ([www.nsf.org](http://www.nsf.org)) and meet USDA 1998 Guidelines. **ANDEROL®** Food Grade lubricants also meet the certification requirements recommended by the National Lubricating Grease Institute (NLGI) and the European Lubricating Grease Institute (ELGI).

### HANDLING & STORAGE

**ANDEROL®** lubricants generally present little hazard in normal handling if ordinary care is exercised. If spilled, cover with inert, absorbent material and remove. Flush the area with water.

Although **ANDEROL®** lubricants are not highly flammable, they will burn and should be kept away from open flames. In case of fire, use water spray, foam, carbon dioxide, or dry chemical.

**ANDEROL®** lubricants should be stored preferably in protected locations to prevent contamination. Do not re-use drums; flush and send to re-conditioner.

**ANDEROL PQAA GREASE #2** is an aluminum complex thickened grease designed for use in food processing machinery. It is a non-toxic, general-purpose grease and can satisfy a wide variety of applications. It provides excellent anti-wear protection and prevent corrosion.

**ANDEROL PQAA GREASE #2** has good water resistance. This product is NSF/H1 registered for use in applications where incidental food contact can occur.

PROPERTIES	TEST METHOD	ANDEROL PQAA GREASE #2
Color	Visual	Transparent
Thickener		Al-complex
Type of Base Oil		Med. White Oil (DAB10)
Operating temperature for long-term lubrication		-20 to +140°C
Short time admissible temperature peak value		+180°C
Dropping Point	ASTM D-2265	>250°C
Worked Penetration	ASTM D-217	265 to 295
Base Oil Viscosity @ 40°C	ASTM D-445	160 mm²/s
Water resistance	DIN 51.807-01	0-90
Corrosion protection	IP 220/85	Corrosion degree 0/1
Designation	DIN 51.502	K 2 N-20

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

### REGISTRATIONS



**ANDEROL®**  
Specialty Lubricants

Groot Egtenrayseweg 23, 5928 PA Venlo, The Netherlands • Tel: +31 (0)77 3960340 • [www.anderol-europe.com](http://www.anderol-europe.com)

This information is furnished without warranty, representation, inducement, or license of any kind except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL® to be accurate. ANDEROL® does not assume any legal responsibility for use of reliance upon it. Only Chemists or chemically qualified lab technicians should carry out tests. Before using any chemicals, read its label and Material Safety Data Sheet.