

Anderol[®] 6220

Anderol[®] Food grade lubricants gears and bearings

Description

H1 High Performance Food Grade Gear Lubricant

Anderol[®] 6220 is a synthetic gear oil based on a mixture of specially selected non-toxic synthetic polyalphaolefins with a specially developed additive system providing excellent oxidative and thermal stability. This product meets the lubrication requirements of gears running in food processing plants.

Anderol[®] 6220 is NSF/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

Anderol[®] Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570.

Anderol[®] 6000 range is available in the grades ISO VG 150, 220, 320, 460 and 680.

Features and Benefits

- Fewer oil changes.
- Reduces energy costs.
- Compatible with mineral oils and most synthetic fluids.
- High and low temperature applications.
- Increased oxidation stability.
- Reduced volatility.

Compatibility

Anderol[®] synthetic hydrocarbon based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an **Anderol[®]** synthetic hydrocarbon based lubricant.

Application

- Gear sets, excluding Worm Gears *)
- Bearings
- Circulating oil systems
- Chains

*) for Worm Gears **Anderol[®] 7220 FG** is recommended.



Anderol[®] 6220

Anderol[®] Food grade lubricants gears and bearings

Technical data*

PROPERTY	METHOD	ANDEROL 6220
ISO VG	ASTM D-2422	220
Appearance @ 20°C	visual	Clear colorless to light yellow liquid
Viscosity @ 40°C, cSt	ASTM D-445	232.7
Viscosity @ 100°C, cSt	ASTM D-445	23.6
Viscosity Index	ASTM D-2270	126
Density @ 15°C, kg/l	ASTM D-1298	0.855
Total Acid Number, mg KOH/g	ASTM D-664	0.5
Flash Point, COC, °C	ASTM D-92	256
Pour Point, °C	ASTM D-97	-42
Demulsibility @ 82°C, min	ASTM D-1401	20
FZG Gear set, Pass Stage	DIN/ISO 14635-1	14
4-Ball Wear, 1200 rpm, 75°C, 40 kg	ASTM D-4172	0.37
4-Ball Weld, kg	ASTM D-2783	160
Fe-8 Bearing Test, Wear of roller sets mg	DIN 51819-3 , D7.5/80-80	1.8

*The analytical data are guide values.



Anderol® 6220

Anderol® Food grade lubricants gears and bearings

Consult safety data sheet (SDS) for additional handling information on **Anderol® 6220**

This product is NSF H1, Kosher, Halal registered and produced in a ISO 21469 certified plant.

For registrations, certificates and approvals please refer to anderol.com

® = registered trade mark

This is a product of Anderol BV
Groot Egtenrayseweg 23
5928PA Venlo
The Netherlands
www.anderol.com

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2021 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America
+1.833.LANXESS
customer.care@lanxess.com

Europe, Middle East & Africa
+31.77.396.0340
customerservice@anderol.com

South & Central America
+55.19.3522.5083
atendimento.cliente@lanxess.com

Asia Pacific
+86.21.6109.6666
Orders.apac@lanxess.com

