

Anderol[®] Bioguard FRHF 68

Anderol[®] Industrial lubricants hydraulics

Description

High Performance Biodegradable Fire Resistant Hydraulic Fluid

Anderol[®] Bioguard FRHF 68 is a high performance biodegradable fire resistant hydraulic fluid. This synthetic based fluid has been specifically designed to meet the most stringent industry requirements, including spray flammability. The formulation utilizes ash-less and silicon free additive technology.

Anderol[®] Bioguard FRHF 68 is fully compatible with mineral oils and polyol ester fluids.

Anderol[®] Bioguard FRHF range is available in the grades ISO VG 46 and 68.

Features and Benefits

- Biodegradable.
- Fire resistant with high fire point.
- Ash-less and silicon free.
- Broad operating temperature range.
- Environmentally friendly.
- Extended lubrication cycles at all temperatures.

Compatibility

The following seals, paints and plastics are recommended for use in contact with **Anderol[®]** synthetic lubricants. Materials not recommended are also shown. For more information on other materials see our 'Compatibility Guide'.

RECOMMENDED:

Viton, High Nitrile Buna N, Teflon, Epoxy Paint, Oil-Resistant Alkyd, Nylon, Delrin, Celcon, PBT

NOT RECOMMENDED:

Neoprene, SBR Rubber, Low Nitrile Buna N, Acrylic Paint, Lacquer, Polystyrene, PVC, ABS

Application

Anderol[®] Bioguard FRHF 68 Lubricant is highly recommended for hydraulic systems in high temperature environments that require a greater degree of fire resistance. This fluid is also suitable for applications where environmentally sensitive products are preferred (such as off-road construction vehicles, tunnel construction and machinery).



Anderol[®] Bioguard FRHF 68Anderol[®] Industrial lubricants hydraulics**Technical data***

PROPERTY	METHOD	ANDEROL BIOGUARD FRHF 68
ISO VG	ASTM D-2422	68
Appearance @ 20°C	visual	Clear colorless to light yellow liquid
Viscosity @ 40°C, cSt	ASTM D-445	65
Viscosity Index	ASTM D-2270	183
Density @ 15°C, kg/l	ASTM D-1298	0.927
Total Acid Number, mg KOH/g	ASTM D-664	1.1
Flash Point, COC, °C	ASTM D-92	302
Pour Point, °C	ASTM D-97	-30
Demulsibility @ 54°C, min	ASTM D-1401	30
Auto-ignition temperature, °C	ASTM E-659	>460
Biodegradability	OECD 301 B	Ready biodegradability 79.9% (28d)

**The analytical data are guide values.*

Anderol[®] Bioguard FRHF 68

Anderol[®] Industrial lubricants hydraulics

Consult safety data sheet (SDS) for additional handling information on **Anderol[®] Bioguard FRHF 68**
For registrations, certificates and approvals please refer to anderol.com

® = registered trade mark

This is a product of Anderol BV
Groot Egtenrayseweg 23
5928PA Venlo
The Netherlands
www.anderol.com

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2021 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America
+1.833.LANXESS
customer.care@lanxess.com

Europe, Middle East & Africa
+31.77.396.0340
customerservice@anderol.com

South & Central America
+55.19.3522.5083
atendimento.cliente@lanxess.com

Asia Pacific
+86.21.6109.6666
Orders.apac@lanxess.com

