

Lubricant Additives Business

Anderol® 6320

Anderol® Food grade lubricants gears and bearings

Description

H1 High Performance Food Grade Gear Lubricant

Anderol[®] **6320** is a synthetic gear oil based on a mixture of specially selected non-toxic synthetic polyalphaolefins with a specially developed additive system providing excellent oxidative and thermal stability. This product meets the lubrication requirements of gears running in food processing plants.

Anderol[®] **6320** is NSF/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

Anderol® Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570.

Anderol® 6000 range is available in the grades ISO VG 150, 220, 320, 460 and 680.

Features and Benefits

- Fewer oil changes.
- Reduces energy costs.
- Compatible with mineral oils and most synthetic fluids.
- High and low temperature applications.
- · Increased oxidation stability.
- Reduced volatility.

Compatibility

Anderol® synthetic hydrocarbon based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an **Anderol**® synthetic hydrocarbon based lubricant.

Application

- Gear sets, excluding Worm Gears *)
- Bearings
- · Circulating oil systems
- · Chains

*) for Worm Gears **Anderol**® **7320 FG** is recommended.

Page 1 of 3

Edition: 2021-01-20





Lubricant Additives Business

Anderol® 6320

 ${\sf Anderol}^{\circledR} \, {\sf Food} \, \, {\sf grade \, lubricants} \, \, {\sf gears} \, \, {\sf and \, bearings} \,$

Technical data*

PROPERTY	METHOD	ANDEROL 6320
ISO VG	ASTM D-2422	320
Appearance @ 20°C	visual	Clear colorless to light yellow liquid
Viscosity @ 40°C, cSt	ASTM D-445	339.8
Viscosity @ 100°C, cSt	ASTM D-445	33.4
Viscosity Index	ASTM D-2270	138
Density @ 15°C, kg/l	ASTM D-1298	0.862
Total Acid Number, mg KOH/g	ASTM D-664	0.5
Flash Point, COC, °C	ASTM D-92	242
Pour Point, °C	ASTM D-97	-42
Demulsibility @ 82°C,min.	ASTM D-1401	15
4-Ball Wear,1200 rpm, 75°C,40 kg	ASTM D-4172	0.35

*The analytical data are guide values.

Page 2 of 3

Edition: 2021-01-20





Lubricant Additives Business

Anderol® 6320

Anderol® Food grade lubricants gears and bearings

Consult product data sheet (SDS) for additional handling information on **Anderol**[®] **6320**This product is NSF H1, Kosher, Halal registered and produced in a ISO 21469 certified plant. For registrations, certificates and approvals please refer to anderol.com

® = registered trade mark

This is a product of Anderol BV Groot Egtenrayseweg 23 5928PA Venlo The Netherlands www.anderol.com

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2021 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America +1.833.LANXESS customer.care@lanxess.com Europe, Middle East & Africa +31.77.396.0340 customerservice@anderol.com South & Central America +55.19.3522.5083 atendimento.cliente@lanxess.com Asia Pacific +86.21.6109.6666 Orders.apac@lanxess.com

Page 3 of 3

Edition: 2021-01-20

