

### Anderol<sup>®</sup> PQAA 22

#### Anderol<sup>®</sup> Food grade lubricants hydraulics

##### Description

##### H1 Food Grade Lubricant General Purpose

**Anderol<sup>®</sup> PQAA 22** is a white oil based general purpose lubricant, combined with high performance additives. It meets most general purpose requirements of machinery.

**Anderol<sup>®</sup> PQAA 22** is NSF/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

**Anderol<sup>®</sup>** Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570.

**Anderol<sup>®</sup> PQAA** range is available in the grades ISO VG 22, 32, 46, 68 & 100.

##### Features and Benefits

- Product was developed with highly stable white oil.
- Product has excellent wear and load carrying capacity.
- Rust and oxidation inhibited.
- Good water separation.

##### Compatibility

**Anderol<sup>®</sup>** white oil based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to this product.

##### Application

H1 Food Approved general purpose lubricant suitable for food manufacturing applications where incidental food contact may occur.

Recommended for use in:

- Hydraulic systems and slide ways
- Pneumatic tools
- Wipe down oil

Can generally be used in all other rotating equipment applications.



**Anderol<sup>®</sup> PQAA 22**Anderol<sup>®</sup> Food grade lubricants hydraulics**Approvals**

- Unilever

**Technical data\***

<b>PROPERTY</b>	<b>METHOD</b>	<b>ANDEROL PQAA 22</b>
ISO VG	ASTM D-2422	22
Appearance @ 20°C	visual	Clear liquid
Viscosity @ 40°C, cSt	ASTM D-445	23.5
Viscosity @ 100°C, cSt	ASTM D-445	4.5
Viscosity Index	ASTM D-2270	110
Density @ 15°C, kg/l	ASTM D-1298	0.8642
Total Acid Number, mg KOH/g	ASTM D-664	0.7
Flash Point, COC, °C	ASTM D-92	182
Pour Point, °C	ASTM D-97	-9
Copper corrosion	ASTM D-130	1a
Demulsibility @ 54°C	ASTM D-1401	5

\*The analytical data are guide values.



### Anderol<sup>®</sup> PQAA 22

### Anderol<sup>®</sup> Food grade lubricants hydraulics

Consult safety data sheet (SDS) for additional handling information on **Anderol<sup>®</sup> PQAA 22**

This product is NSF H1, Kosher, Halal registered and produced in a ISO 21469 certified plant.

For registrations, certificates and approvals please refer to [anderol.com](http://anderol.com)

® = registered trade mark

This is a product of Anderol BV  
Groot Egtenrayseweg 23  
5928PA Venlo  
The Netherlands  
[www.anderol.com](http://www.anderol.com)

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2023 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America  
+1.833.LANXESS  
[customer.care@lanxess.com](mailto:customer.care@lanxess.com)

Europe, Middle East & Africa  
+31.77.396.0340  
[customerservice@anderol.com](mailto:customerservice@anderol.com)

South & Central America  
+55.19.3522.5083  
[atendimento.cliente@lanxess.com](mailto:atendimento.cliente@lanxess.com)

Asia Pacific  
+86.21.6109.6666  
[Orders.apac@lanxess.com](mailto:Orders.apac@lanxess.com)

