

### Anderol<sup>®</sup> 7150 FG

Anderol<sup>®</sup> Food grade lubricants gears and chains

#### Description

##### H1 High Performance Food Grade Gear & Chain Lubricant

**Anderol<sup>®</sup> 7150 FG** is a high performance product, designed primarily for industrial worm gear applications in the food & beverage industry. It may also be considered as a general purpose gear lubricant or to lubricate chains and ways. This fluid is a synthetic Polyalkylene Glycol (PAG) based fluid that provides excellent thermal and oxidative stability, load carrying ability and sludge-free operation over a wide temperature range. The PAG base stock is enhanced with a special mixture of additives providing thermal oxidation stability and anti-wear performance.

**Anderol<sup>®</sup> 7150 FG** is NSF/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

**Anderol<sup>®</sup>** Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570.

#### Features and Benefits

- Long life, fewer oil changes.
- High water tolerance.
- Very good heat dissipation.
- Improved thermal stability.
- Increased oxidative stability.
- Extends equipment life.
- High and low temperature operations.
- Excellent corrosion inhibition.
- Reduced volatility.
- No sludge formation.

#### Compatibility

**Anderol<sup>®</sup> 7150 FG** is PAG based, therefore thorough cleaning is recommended when mixing with any other chemistries, such as petroleum based (mineral oils) and/or PAO (Polyalphaolefins).

When changing over from a conventional mineral oil care should be taken to minimize contamination caused by decomposition material from the previous lubricant.

Thorough cleaning with an ester followed by a light petroleum solvent is advisable.



### Anderol<sup>®</sup> 7150 FG

Anderol<sup>®</sup> Food grade lubricants gears and chains

#### Application

- Worm gears
- Chains and ways, including high water containing applications.

They can also be used in:

- Low speed gear sets
- Bearings
- Circulation systems
- Almost all gear sets requiring an ISO 150 or 220 VG oil.

#### Technical data\*

PROPERTY	METHOD	ANDEROL 7150 FG
ISO VG	ASTM D-2422	150
Appearance @ 20°C	visual	Clear liquid
Viscosity @ 40°C, cSt	ASTM D-445	162.5
Viscosity @ 100°C, cSt	ASTM D-445	26.8
Viscosity Index	ASTM D-2270	202
Density @ 15°C, kg/l	ASTM D-1298	0.9976
Total Acid Number, mg KOH/g	ASTM D-664	1.6
Flash Point, COC, °C	ASTM D-92	278
Pour Point, °C	ASTM D-97	-39
4-Ball Wear, 1200 rpm, 75°C, 40kg	ASTM D-4172	0.35
4-Ball Weld, kg	ASTM D-2783	160
Copper corrosion	ASTM D-130	1a

\*The analytical data are guide values.



### Anderol<sup>®</sup> 7150 FG

#### Anderol<sup>®</sup> Food grade lubricants gears and chains

Consult safety data sheet (SDS) for additional handling information on **Anderol<sup>®</sup> 7150 FG**  
This product is NSF H1, Kosher, Halal registered and produced in a ISO 21469 certified plant.  
For registrations, certificates and approvals please refer to [anderol.com](http://anderol.com)

® = registered trade mark

This is a product of Anderol BV  
Groot Egtenrayseweg 23  
5928PA Venlo  
The Netherlands  
[www.anderol.com](http://www.anderol.com)

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2021 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America  
+1.833.LANXESS  
[customer.care@lanxess.com](mailto:customer.care@lanxess.com)

Europe, Middle East & Africa  
+31.77.396.0340  
[customerservice@anderol.com](mailto:customerservice@anderol.com)

South & Central America  
+55.19.3522.5083  
[atendimento.cliente@lanxess.com](mailto:atendimento.cliente@lanxess.com)

Asia Pacific  
+86.21.6109.6666  
[Orders.apac@lanxess.com](mailto:Orders.apac@lanxess.com)

