

Anderol® Chain Oil XL 220-A

Anderol® Industrial lubricants chains

Description

High Temperature Synthetic Chain Oil-A

Anderol® Chain Oil XL 220-A is a high performance polyolester based chain oil designed for use in both tunnel ovens and spiral ovens. The product uses proven technology to provide high flash and fire points.

Anderol® Chain Oil XL 220-A prevents wear and minimizes deposits with a natural detergency to maintain cleaner chains with fewer operational problems.

Features and Benefits

- High flash and fire point.
- Excellent anti-wear characteristics.
- Excellent thermal and oxidative stability.
- Reduces chain and sprocket wear.
- Natural detergency.
- Exceptionally low deposit forming tendencies.
- Keeps chains clean and prevents carbon residue build-up.

Application

Anderol® Chain Oil XL 220-A is designed for use in tunnel ovens and spiral ovens. The product can also be used in the following applications:

- Conveyor systems
- Printing and coating operations
- Wood-forming machinery such as that used in the oriented strand board or plywood industry
- Other applications requiring a high temperature bearing, cam or slide lubricant

Nominal operating range -10 to 260°C.



Anderol[®] Chain Oil XL 220-AAnderol[®] Industrial lubricants chains**Technical data***

PROPERTY	METHOD	ANDEROL CHAIN OIL XL 220-A
ISO VG	ASTM D-2422	220
Viscosity @ 40°C, cSt	ASTM D-445	219.3
Viscosity @ 100°C, cSt	ASTM D-445	19
Viscosity Index	ASTM D-2270	97
Specific Gravity @ 15.6°C	ASTM D-4052	0.975
Flash Point, °C	ASTM D-92	290
Pour Point, °C	ASTM D-97	-22
Fire Point, °C	ASTM D-92	348
Auto-ignition point, °C	ASTM E-659	>425
4-Ball Wear Scar Diameter, mm (1hr / 75°C / 40 kg / 1200 rpm)	ASTM D-4172	0.4

**The analytical data are guide values.*

Anderol[®] Chain Oil XL 220-A

Anderol[®] Industrial lubricants chains

Consult safety data sheet (SDS) for additional handling information on **Anderol[®] Chain Oil XL 220-A**
For registrations, certificates and approvals please refer to anderol.com

® = registered trade mark

This is a product of Anderol BV
Groot Egtenrayseweg 23
5928PA Venlo
The Netherlands
www.anderol.com

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2025 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America
+1.833.LANXESS
customer.care@lanxess.com

Europe, Middle East & Africa
+31.77.396.0340
customerservice@anderol.com

South & Central America
+55.19.3522.5083
atendimento.cliente@lanxess.com

Asia Pacific
+86.21.6109.6666
Orders.apac@lanxess.com

