

Anderol[®] 5680 XEP

Anderol[®] Industrial lubricants gears and bearings

Description

Synthetic Gear and Bearing Lubricant

Anderol[®] 5680 XEP is a synthetic based, high performing gear lubricant to be used in industrial equipment. It was designed to withstand heavy loads and severe conditions resulting in very good micro pitting resistance. The PAO based product gives superior advantages to the mineral oil based products, especially with regards to low pour point, oxidation stability and energy consumption.

Anderol[®] 5000 XEP range is available in the grades ISO VG 150, 220, 320, 460, 680 and 1000.

Anderol[®] 5680 XEP meets or exceeds the requirements of:
ANSI/AGMA 9005 (table 3)
AISE 224 (formerly USS 224)
DIN 51.517

Features and Benefits

- Excellent oxidation and thermal stability.
- Wide operating temperature range.
- Lower maintenance costs.
- Excellent load carrying ability.
- Extended lubricant life.
- Improved cleanliness.
- Excellent anti-wear properties.
- Very good rust and copper corrosion prevention.
- Compatible with petroleum oils, therefore allowing minimal effort to changeover.

Compatibility

The following seals, paints and plastics are recommended for use in contact with **Anderol[®]** synthetic lubricants. Materials not recommended are also shown. For more information on other materials see our 'Compatibility Guide'.

RECOMMENDED:

Viton, High Nitrile Buna N, Teflon, Epoxy Paint, Oil-Resistant Alkyd, Nylon, Delrin, Celcon, PBT

NOT RECOMMENDED:

Neoprene, SBR Rubber, Low Nitrile Buna N, Acrylic Paint, Lacquer, Polystyrene, PVC, ABS



Anderol[®] 5680 XEP

Anderol[®] Industrial lubricants gears and bearings

Application

- Particularly suited for gear applications exposed to extreme service conditions.
- All types of enclosed gear drives.
- Bearings, including plain rolling elements and antifriction types.
- Enclosed gear cases and speed reducers.

Approval

- Rossi Motoriduttori



Anderol[®] 5680 XEP

Anderol[®] Industrial lubricants gears and bearings

Technical data*

PROPERTY	METHOD	ANDEROL 5680 XEP
ISO VG	ASTM D-2422	680
Appearance @ 20°C	visual	Clear Yellow Liquid
Viscosity @ 40°C, cSt	ASTM D-445	642.7
Viscosity @ 100°C, cSt	ASTM D-445	60.8
Viscosity Index	ASTM D-2270	163
Density @ 15°C, kg/l	ASTM D-1298	0.910
Total Acid Number, mg KOH/g	ASTM D-664	0.5
Flash Point, °C	ASTM D-92	245
Pour Point, °C	ASTM D-97	-36
Foam, Sequence I, II ml	ASTM-892	10
Micro pitting Resistance Test	FVA, 54/11	High
FZG Gear test, Pass Stage	DIN/ISO 14635-1	14
4-Ball Wear, 1200 rpm, 40 kg, 75 °C	ASTM D-4172	0.55
4-Ball Weld, kg	ASTM D-2783	250
FE-8 Industrial Gear requirements	DIN 51819 T1-T3	
Bearing Lubrication Test J1 (FAG Step I)		Pass
Bearing Lubrication Test J2 (FAG Step II)		Pass
FAG Wind Power requirements		
Wind power Level 3 Test L11 (FAG Step III)		Pass
Oil suitability for Wind Energy Plant Applications (FAG Step IV)		Pass

*The analytical data are guide values.



Anderol[®] 5680 XEP

Anderol[®] Industrial lubricants gears and bearings

Consult safety data sheet (SDS) for additional handling information on **Anderol[®] 5680 XEP**
For registrations, certificates and approvals please refer to anderol.com

® = registered trade mark

This is a product of Anderol BV
Groot Egtenrayseweg 23
5928PA Venlo
The Netherlands
www.anderol.com

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2021 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America
+1.833.LANXESS
customer.care@lanxess.com

Europe, Middle East & Africa
+31.77.396.0340
customerservice@anderol.com

South & Central America
+55.19.3522.5083
atendimento.cliente@lanxess.com

Asia Pacific
+86.21.6109.6666
Orders.apac@lanxess.com

