

QUALITY LUBRICATES.



Anderol® lubricants in sintered bearings

The type of lubricant that is used in a sintered bearing has a direct impact on the lifespan of the bearing and how well it works in its application. Sintered bearings perform better with Anderol® lubricants. Our products provide low friction and reduce wear and noise. Discover our solutions. anderol.com

X **Anderol®**

QUALITY WORKS.

LANXESS
Energizing Chemistry

SINTERED BEARINGS

CASE STUDY

Sintered or self-lubricating bearings

Unlike non-porous bearings which require lubricating oil to be applied during operation, the oil-impregnated sintered bearing is always well-lubricated. The lubricating oil is contained inside the porous bearing material.

With a pore volume of between 15 and 30 percent, the pores inside the sintered bearing are used as an oil reservoir for the bearing's entire service life so that friction never becomes a concern.

During operation, the oil reservoir inside the bearing produces a permanent lubricating film on the sliding surface and enables the lubricant to circulate in the bearing.

Applications

Oil-impregnated sintered sliding bearings are a fundamental element in many different machineries. They can be used in a variety of smaller electric motors and household actuators, in the consumer goods industry, automotive applications and in general mechanical engineering applications.

Typical automotive applications include bearings for windshield wipers, window mechanisms, seat adjusters, sunroofs and fan motors.

Sintered bearings are also found in many general household appliances, such as microwaves, air fryers and juicers, as well as office equipment, electric drills and fishing reels.

Manufacturing process

The process to create oil-impregnated sintered bearings is called powder metallurgy. Firstly metal powder (typically iron, copper, tin or bronze) is mixed with powder additives; the next step is the forming or shaping of the bearings, followed by sintering; and lastly the oil is impregnated. The pressure inside the oil impregnation tank is reduced to the atmospheric pressure or lower so that the oil is easily infused into the product.

Selecting the right lubricant

The type of lubricating oil impregnated into the bearing is selected based on the bearing load, the sliding speed, and the bearing temperature. Poor lubricating oil can cause seizures, abnormal wear, noise, and shorten the life expectancy of the bearing.

For the standard bearing operating temperature range (0 to 80°C), mineral-based lubricating oil can be used. If the operating temperature range is expected to be higher or lower than this range, a synthetic-based lubricating oil suitable for the application temperature is selected. Ester based lubricants have excellent wetting properties, load carrying and greater material consistency compared to mineral oils.

Bearing life and the importance of lubricating oil

The life of the oil-impregnated sintered bearing is determined by the rate of consumption of the lubricating oil infused into the bearing. Once 40 percent of the oil has been consumed, bearing wear begins to accelerate and performance deteriorates accordingly. Therefore, once the residual lubricating oil drops to 60 percent, the bearing is generally regarded as having reached the end of its service life. In addition, the lubricating oil is adversely affected by high temperature, and the maximum allowable temperature is generally considered to be 80°C for mineral oils and 130°C for synthetic oils.

Using a synthetic lubricating oil, the oil-impregnated sintered bearing can be used for a longer period of time, has superior durability at high temperatures and low noise levels.

Anderol® solutions

Anderol®	Base fluid	Viscosity ISO VG
465	Ester	68
5000 PLUS range	PAO/Ester	150, 220, 320, 460, 680



ANDEROL® 465

SUCCESS STORY

The situation

A Chinese powder metallurgy parts manufacturer produces mainly copper, iron and copper-iron based oil-impregnated sintered bearings, typically used in motors for small home appliances, such as microwaves, air fryers and juicers.

Price and noise are the main considerations of the customers of these sintered bearings. Therefore, in order to reduce costs, an ISO 68 mineral hydraulic oil was used for impregnating the bearings.

Some customers complained of excessive noise, slow startup at low temperatures, inability to withstand high temperatures and an inadequate service life.

The solution

The customer switched to **Anderol® 465** – an ISO 68 synthetic di-ester based lubricant that is formulated to offer extended lubrication over a wide temperature range, resist gumming and speed fluctuations and to minimize wear. **Anderol® 465** has excellent oxidation resistance, reduces friction, good load carrying, excellent corrosion and rust protection, and the nominal operating temperature range is between -35°C to 130°C (-35° F to 270° F). **Anderol® 465** is suitable as an impregnating fluid for sintered metal bearings.

The result

The previous product was an ISO 68 hydraulic oil. Tests were carried out at 130 degrees Celsius and the results as follows:

- Poor high temperature performance (oil loss within less than one hour)
- Service life of approximately 300 hours
- The noise reached more than 70db and the bearing was badly worn.

The customer was recommended **Anderol® 465** as a replacement oil. Tests were carried out at 130 degrees Celsius and the results were as follows:

- Excellent high temperature performance
- Service life of more than 1000 hours
- The noise level was significantly reduced



Comparison table

	ISO 68 hydraulic lubricant	Anderol® 465
Time, oil loss at 130°C	<1 hr	~3 hrs
Bearing service life	~300 hrs	>1000 hrs
Noise level	>70db	<60db

ANDEROL® 5000 PLUS range

SUCCESS STORY

The situation

A Turkish manufacturer of kitchen and home appliances noticed that their blenders and mixers were making too much noise. While conducting an inspection to find the root cause of the problem, they noticed wear on the metal sintered bearings in the mixer and blender shafts.

The solution

Initially, we suggested Anderol® 465 – an ISO 68 synthetic di-ester based lubricant that commonly used in sintered bearings. This product was not the perfect fit for the application, and after assessment we advised to use a PAO/Ester based lubricant with higher viscosity.

Anderol® 5460 PLUS, is an ISO VG 460, PAO/Ester based lubricant, suited for gear applications exposed to extreme service conditions, all types of enclosed gear drives, bearings, including plain rolling elements and anti-friction types, enclosed gear cases and speed reducers.

The result

Using sintered bearings impregnated with Anderol® 5460 PLUS, the noise dissipated and energy savings were observed.

Energy savings are indicative of Anderol® 5460 PLUS's low coefficient of friction. In addition, the lubricant has outstanding anti-wear properties, a wide operating temperature range, and extended lubricant life.

They began incorporating Anderol® 5320 and 6460 PLUS into their sintered bearings.





Anderol BV
Groot Egtenrayseweg 23
5928 PA Venlo
The Netherlands

www.anderol.com
info@anderol.com
+31 (0)77 396 0340

North America
+1 833 LANXESS
customer.care@lanxess.com

South & Central America
+55 19 3522 5083
atendimento.cliente@lanxess.com

Asia Pacific
+86 21 6109 6666
Orders.apac@lanxess.com

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided – especially that contained in our safety data and technical information sheets – and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

Unless specified to the contrary, the values given have been established or standardized test specimens. The figures should be regarded as guide values and not as binding minimum values. Kindly note that the results refer exclusively to the specimens tested. Under certain conditions, the test results established can be affected to a considerable extent by the processing conditions and manufacturing process.

©2024 Anderol BV

Anderol®, LANXESS and the LANXESS logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.